

DigiTRAK *F5+* **TRANSMITTERS**











**LEARN
MORE ABOUT
TRANSMITTERS**

MADE IN U.S.A 

POWERED BY  **DIGITAL CONTROL**

TRANSMITTER FEATURES

QUALITY, DURABILITY, AND TRUSTED PERFORMANCE

-  V2 Multi-power Transmitter
-  Full Scale 0.1 Pitch
-  V2 Increased Depth
-  Fluid Pressure
-  Rechargeable LiR Adapter
-  DigiTrak® Falcon Pairing
-  V2 Custom Battery Life
-  Sub-K™ Rebar Capacity

V2 Wideband VS Sub-K™ Rebar

Our Wideband transmitters include V2 Multi-Power which gives you three selectable power modes to dial in your ideal balance of power and battery life, while also supporting Fluid Pressure, Full Scale Sensitive Pitch and **over 1000 frequencies** to help you avoid active and passive interference.

Our Industry exclusive Sub-k™ Rebar transmitters utilize ultra low range frequencies geared towards helping you navigate under reinforced concrete, while also supporting Fluid Pressure and Full Scale Sensitive Pitch. These transmitters support dual modes that can be changed below ground; Sub-k mode with low power range and Standard Power mode with **over 300 frequencies** when depth and interference become an issue.




Now when using with the DigiTrak Falcon F5+ you can get higher data speeds on V2 low power for the fastest updates ever!



ONE TRANSMITTER, THREE MODES

GET THE JOB DONE WITH WIDEBAND V2 MULTI-POWER TRANSMITTERS AND SUPERCCELL™

Drilling Deep? Use High Power Mode.			Drilling? Use Standard Mode			Drilling Shallow? Use Low Power Mode.					
15"	14 Hours	125 ft Depth range	160 ft Data range	15"	80 Hours	100 ft Depth range	125 ft Data range	15"	140 Hours	65 ft Depth range	80 ft Data range
19"	14 Hours	160 ft Depth range	200 ft Data range	19"	40 Hours	125 ft Depth range	150ft Data range	19"	120 Hours	100 ft Depth range	125 ft Data range
24"	14 Hours	180 ft Depth range	220 ft Data range	24"	40 Hours	160 ft Depth range	185 ft Data range	24"	120 Hours	120 ft Depth range	140 ft Data range

*Actual ranges and battery life will vary based on interference, transmitter housing, frequency and other factors.

@2023 Digital Control Incorporated, all rights reserved.

TRANSMITTER SPECIFICATIONS

THE F5+ FAMILY GIVES YOU MORE OPTIONS



Product #	V2 Wideband w/PSI			Sub-k™ Rebar w/PSI		
	FT5p	FT5Lp	FT5XLp	FTR5s	FTR5p	FTR5Lp
V2 Multi-Power	✓	✓	✓			
V2 Increased Depth	✓	✓	✓			
LiR Rechargeable	✓	✓	✓		✓	✓
Sub-K Capacity				✓	✓	✓
V2 Custom Battery Life	✓	✓	✓			
Fluid Pressure	✓	✓	✓		✓	✓
FSSP 0.1% Pitch	✓	✓	✓		✓	✓
Falcon Pairing	✓	✓	✓	✓	✓	✓



Rechargeable Lithium-Ion batteries compatible with new adapter!

Warranty Registration

All 15, 19, and 24 inch Transmitters backed by our standard 3 year/500 hour warranty with an available extended 5 year/750 hour warranty. Our 8 inch Transmitters are backed by a 90 day warranty.